

AMENDMENTS TO THE CLAIMS

Please amend the claims as follows:

1-18. (Cancelled)

19. (Previously Presented) A receiver unit in a wireless communication system, comprising:

a signal detector operative to determine a metric for a data transmission hypothesized to have been received;

a threshold computation unit operative to determine a threshold based on the hypothesized data transmission; and

a comparator operative to receive the metric and the threshold and provide an output indicating whether or not the data transmission is deemed to have been received.

20. (Original) The receiver unit of claim 19, wherein the threshold is determined based on received pilot symbols for the hypothesized data transmission.

21. (Original) The receiver unit of claim 20, wherein the threshold is further determined based on received data symbols for the hypothesized data transmission.

22. (Original) The receiver unit of claim 19, wherein the metric relates to signal energy of the hypothesized data transmission.

23. (Original) The receiver unit of claim 19, wherein the signal detector is operative to determine the metric based on a plurality of received signals for a plurality of antennas, and wherein the threshold computation unit is operative to determine the threshold based on the plurality of received signals.

24. (Currently Amended) A method of detecting data transmissions in a wireless multiple-access communication system, comprising:

first processing received data symbols for a data transmission hypothesized to have been received to provide remodulated symbols that are estimates of transmitted data symbols; ~~and~~
second processing the received data symbols and the remodulated symbols to provide a detector output that indicates whether or not the data transmission is deemed to have been received;
and

determining a threshold to use for the hypothesized data transmission, and wherein the detector output is further determined based on the threshold,

wherein the second processing includes
determining a metric based on the received data symbols and the remodulated symbols, and
comparing the metric against the threshold, and wherein the detector output is based on the
comparing.

25. (Original) The method of claim 24, wherein the first processing includes demodulating the received data symbols to provide recovered symbols, decoding the recovered symbols to provide decoded data, and re-encoding the decoded data to provide the remodulated symbols.

26-27. (Canceled)

28. (Original) A method of detecting data transmissions in a wireless multiple-access communication system, comprising:

determining a metric for a data transmission hypothesized to have been received;
determining a threshold for the hypothesized data transmission based on samples received for the hypothesized data transmission; and
comparing the metric against the threshold to provide an output indicating whether or not the data transmission is deemed to have been received.

29-30. (Canceled)

31. (Original) An apparatus in a wireless multiple-access communication system, comprising:

means for determining a metric for a data transmission hypothesized to have been received;
means for determining a threshold for the hypothesized data transmission based on samples received for the hypothesized data transmission; and
means for comparing the metric against the threshold to provide an output indicating whether or not the data transmission is deemed to have been received.

32. (Previously Presented) A memory unit having software codes stored thereon for performing a method of detecting data transmissions in a wireless multiple-access communication system, the method comprising:

determining a metric for a data transmission hypothesized to have been received;
determining a threshold for the hypothesized data transmission based on samples received for the hypothesized data transmission; and
comparing the metric against the threshold to provide an output indicating whether or not the data transmission is deemed to have been received.

33. (Previously Presented) The memory unit of claim 32, wherein the threshold is determined based on received pilot symbols for the hypothesized data transmission.

34. (Previously Presented) The memory unit of claim 33, wherein the threshold is further determined based on received data symbols for the hypothesized data transmission.

35. (Previously Presented) The memory unit of claim 32, wherein the metric relates to signal energy of the hypothesized data transmission.

36. (Previously Presented) The memory unit of claim 32, the method further comprising determining the metric based on a plurality of received signals for a plurality of antennas, and determining the threshold based on the plurality of received signals.

37. (Currently Amended) A memory unit having software codes stored thereon for performing a method of detecting data transmissions in a wireless multiple-access communication system, the method comprising:

first processing received data symbols for a data transmission hypothesized to have been received to provide remodulated symbols that are estimates of transmitted data symbols; ~~and~~

second processing the received data symbols and the remodulated symbols to provide a detector output that indicates whether or not the data transmission is deemed to have been received; and

determining a threshold to use for the hypothesized data transmission, and wherein the detector output is further determined based on the threshold,

wherein the second processing includes:

determining a metric based on the received data symbols and the remodulated symbols, and comparing the metric against the threshold, and wherein the detector output is based on the comparing.

38. (Previously Presented) The memory unit of claim 37, wherein the first processing includes:

demodulating the received data symbols to provide recovered symbols,
decoding the recovered symbols to provide decoded data, and
re-encoding the decoded data to provide the remodulated symbols.

39-40. (Canceled)

41. (Previously Presented) An apparatus, comprising:

a processor capable of executing instructions for performing a method of detecting data transmissions in a wireless multiple-access communication system, the method comprising:

determining a metric for a data transmission hypothesized to have been received;
determining a threshold for the hypothesized data transmission based on samples received for the hypothesized data transmission; and

comparing the metric against the threshold to provide an output indicating whether or not the data transmission is deemed to have been received; and
a memory unit communicatively coupled to the processor having the instructions stored therein.

42. (Previously Presented) The apparatus of claim 41, wherein the threshold is determined based on received pilot symbols for the hypothesized data transmission.

43. (Previously Presented) The apparatus of claim 42, wherein the threshold is further determined based on received data symbols for the hypothesized data transmission.

44. (Previously Presented) The apparatus of claim 41, wherein the metric relates to signal energy of the hypothesized data transmission.

45. (Previously Presented) The apparatus of claim 41, the method further comprising determining the metric based on a plurality of received signals for a plurality of antennas, and determining the threshold based on the plurality of received signals.

46. (Currently Amended) An apparatus, comprising:
a processor capable of executing instructions for performing a method of detecting data transmissions in a wireless multiple-access communication system, the method comprising:
first processing received data symbols for a data transmission hypothesized to have been received to provide remodulated symbols that are estimates of transmitted data symbols; ~~and~~
second processing the received data symbols and the remodulated symbols to provide a detector output that indicates whether or not the data transmission is deemed to have been received;
and
determining a threshold to use for the hypothesized data transmission, and wherein the detector output is further determined based on the threshold;
wherein the second processing includes determining a metric based on the received data symbols and the remodulated symbols and comparing the metric against the threshold, and wherein the detector output is based on the comparing;

and
a memory unit communicatively coupled to the processor having the instructions stored therein.

47. (Previously Presented) The apparatus of claim 46, wherein the first processing includes:

demodulating the received data symbols to provide recovered symbols,
decoding the recovered symbols to provide decoded data, and
re-encoding the decoded data to provide the remodulated symbols.

48-49. (Canceled)

50-51. (Canceled)

52. (Previously Presented) The method of claim 28, wherein the threshold is determined based on received pilot symbols for the hypothesized data transmission.

53. (Previously Presented) The method of claim 52, wherein the threshold is further determined based on received data symbols for the hypothesized data transmission.

54. (Previously Presented) The method of claim 28, wherein the metric relates to signal energy of the hypothesized data transmission.

55. (Previously Presented) The method of claim 28, further comprising determining the metric based on a plurality of received signals for a plurality of antennas, and determining the threshold based on the plurality of received signals.